

型号 Model No.	规格 Specification			基材 Substrate	技术指标 Technical Data				适用范围 Application scope
	厚度 (um) Thickness(um)	宽度(mm) Width (mm)	长度(m) Length (m)		剥离强度(g/50mm) Adhesive strength(g/50mm)	断裂伸长率 (%) Elongation (%)	耐刮 Scratch	耐温 (℃) Temperature (℃)	
L30TR	30	30-1500	100-1000	PE	5-48	≥300		60	低粘性保护膜 ，易贴易撕，适用于亚克力、PVC光面板、ABS光面板、玻璃板材、镜钢板、塑胶板等各类表面光滑的产品。 Protective film with low adhesive is easy to apply and easy to remove. Suitable for surface protection on Acrylic (PMMA) sheet, PVC sheet, ABS sheet, Mirrored steel plate, anodized aluminum, plastic board and many more products of high gloss surface
L30BL	30	30-1500	100-1000	PE	5-48	≥300		60	
L30WH	30	30-1500	100-1000	PE	5-48	≥300		60	
L40TR	40	30-1500	100-1000	PE	5-48	≥300		60	
L40BL	40	30-1500	100-1000	PE	5-48	≥300		60	
L40WH	40	30-1500	100-1000	PE	5-48	≥300		60	
L50TR	50	30-1500	100-1000	PE	5-48	≥300		60	
L50BL	50	30-1500	100-1000	PE	5-48	≥300		60	
L50WH	50	30-1500	100-1000	PE	5-48	≥300		60	
ML30TR	30	30-1500	100-1000	PE	50-150	≥300		60	
ML30BL	30	30-1500	100-1000	PE	50-150	≥300		60	
ML30WH	30	30-1500	100-1000	PE	50-150	≥300		60	
ML40TR	40	30-1500	100-1000	PE	50-150	≥300		60	
ML40BL	40	30-1500	100-1000	PE	50-150	≥300		60	
ML40WH	40	30-1500	100-1000	PE	50-150	≥300		60	
ML50TR	50	30-1500	100-1000	PE	50-150	≥300		60	
ML50BL	50	30-1500	100-1000	PE	50-150	≥300		60	
ML50WH	50	30-1500	100-1000	PE	50-150	≥300		60	
M30TR	30	30-1500	100-1000	PE	160-230	≥300		60	
M30BL	30	30-1500	100-1000	PE	160-230	≥300		60	
M30WH	30	30-1500	100-1000	PE	160-230	≥300		60	
M40TR	40	30-1500	100-1000	PE	160-230	≥300		60	
M40BL	40	30-1500	100-1000	PE	160-230	≥300		60	
M40WH	40	30-1500	100-1000	PE	160-230	≥300		60	
M50TR	50	30-1500	100-1000	PE	160-230	≥300		60	
M50BL	50	30-1500	100-1000	PE	160-230	≥300		60	
M50WH	50	30-1500	100-1000	PE	160-230	≥300		60	
M60TR	60	30-1500	100-1000	PE	160-230	≥300		60	
M60BL	60	30-1500	100-1000	PE	160-230	≥300		60	
M60WH	60	30-1500	100-1000	PE	160-230	≥300		60	
H40TR	40	30-1500	100-1000	PE	370-430	≥300		60	
H40BL	40	30-1500	100-1000	PE	370-430	≥300		60	
H40WH	40	30-1500	100-1000	PE	370-430	≥300		60	
H50TR	50	30-1500	100-1000	PE	370-430	≥300		60	
H50BL	50	30-1500	100-1000	PE	370-430	≥300		60	
H50WH	50	30-1500	100-1000	PE	370-430	≥300		60	
H50BW	50	30-1500	100-1000	PE	370-430	≥300		60	
H60TR	60	30-1500	100-1000	PE	370-430	≥300		60	
H60BL	60	30-1500	100-1000	PE	370-430	≥300		60	
H60WH	60	30-1500	100-1000	PE	370-430	≥300		60	
H60BW	60	30-1500	100-1000	PE	370-430	≥300		60	
H70TR	70	30-1500	100-1000	PE	370-430	≥300		60	
H70BL	70	30-1500	100-1000	PE	370-430	≥300		60	
H70WH	70	30-1500	100-1000	PE	370-430	≥300		60	
H70BW	70	30-1500	100-1000	PE	370-430	≥300		60	
H80TR	80	30-1500	100-1000	PE	370-430	≥300		60	
H80BL	80	30-1500	100-1000	PE	370-430	≥300		60	
H80WH	80	30-1500	100-1000	PE	370-430	≥300		60	
H80BW	80	30-1500	100-1000	PE	370-430	≥300		60	
VH50TR	50	30-1500	100-1000	PE	540-610;1000-1500	≥300		60	
VH50BL	50	30-1500	100-1000	PE	540-610;1000-1500	≥300		60	
VH50WH	50	30-1500	100-1000	PE	540-610;1000-1500	≥300		60	
VH50BW	50	30-1500	100-1000	PE	540-610;1000-1500	≥300		60	
VH70TR	70	30-1500	100-1000	PE	540-610;1000-1500	≥300		60	
VH70BL	70	30-1500	100-1000	PE	540-610;1000-1500	≥300		60	
VH70WH	70	30-1500	100-1000	PE	540-610;1000-1500	≥300		60	
VH70BW	70	30-1500	100-1000	PE	540-610;1000-1500	≥300		60	
VH80TR	80	30-1500	100-1000	PE	540-610;1000-1500	≥300		60	
VH80BL	80	30-1500	100-1000	PE	540-610;1000-1500	≥300		60	
VH80W	80	30-1500	100-1000	PE	540-610;1000-1500	≥300		60	
VH80BW	80	30-1500	100-1000	PE	540-610;1000-1500	≥300		60	
VH90TR	90	30-1500	100-1000	PE	540-610;1000-1500	≥300		60	
VH90BL	90	30-1500	100-1000	PE	540-610;1000-1500	≥300		60	
VH90W	90	30-1500	100-1000	PE	540-610;1000-1500	≥300		60	
VH90BW	90	30-1500	100-1000	PE	540-610;1000-1500	≥300		60	
VH100TR	100	30-1500	100-1000	PE	540-610;1000-1500	≥300		60	
VH100BL	100	30-1500	100-1000	PE	540-610;1000-1500	≥300		60	
VH100WH	100	30-1500	100-1000	PE	540-610;1000-1500	≥300		60	
VH100BW	100	30-1500	100-1000	PE	540-610;1000-1500	≥300		60	